A high-quality, eco-friendly & reliable partner for your wraps!

FiberFilm[™] is a unique high efficiency stretch film with reinforcement elements (fibers) that increase Tear Resistance. **FiberFilm™** for machine applications is specially designed for either Semi-Automatic Wrapping Machines or Power Pre-Stretch Wrappers.





for Semi-Automatic Wrapping Machines with

alpha-HD

вета-но

High Demanding applications.

alpha-gp General Purpose applications.

BRAKE TENSION SYSTEM

асрна-с Light applications.



High Demanding applications

pre-stretch ratio up to 180%.

for Power Pre-Stretch Wrapping Machines with

вета-др

General Purpose applications pre-stretch ratio up to 170%.

PRE-STRETCH RATIO UP TO 180%

вета-с **Light** applications pre-stretch ratio up to 160%.



for Power Pre-Stretch Wrapping Machines with PRE-STRETCH RATIO UP TO 250%

Gamma-HD

High Demanding applications pre-stretch ratio up to 250%.

Gamma-GP

General Purpose applications pre-stretch ratio up to 240%.

Gamma-L

Light applications pre-stretch ratio up to 230%.



for Advanced Technology Wrapping Machines with

DELTA-HD

High Demanding applications pre-stretch ratio up to 350%.

DELTA-GP

General Purpose applications pre-stretch ratio up to 300%.

DELTA-L

PRE-STRETCH RATIO UP TO 350%

Light applications pre-stretch ratio up to 280%.

Trias Packaging Company BV - Van Schijndelstraat 9 - 5145 RE - Waalwijk info@tpc-nederland.nl www.tpc-nederland.nl Telefoon +31 (0) 416 543110